

BSPP 60° CONE FITTINGS



Most Cost Effective, World Class Quality
Flow Control Components for Wide Range
of Industries and Applications

The Secret of our success is Ritualistic continuous improvement of our products and process



THE COMPANY

DAWSONS-TECH is an ISO 9001:2015 certified manufacturing company offers wide range of **Consistent and Reliable World Class Quality Flow Control Components** used in Fluid / Gas Control systems in a wide range of Industries.

MANUFACTURING:

DAWSONS-TECH established its comprehensive state of art manufacturing and testing facility installing various CNC Turning Centre and CNC Turnmill Centre, Vertical Machining Centre, etc. with the highly motivated and dedicated team of employees in place. This facilitate us to design and manufacture our product range under stringent quality checks and measurements that ensures "A TOTAL CUSTOMER SATISFACTIONS WITH ZERO DEFECT PRODUCTS".

QUALITY:

DAWSONS-TECH persues not only performance of its products but also ensures "TOTAL QUALITY CONTROL MANAGEMENT SYSTEMS IN ACCORDANCE TO ISO 9001:2015" which is achieved by alerting and educating each and every employee, the importance of quality and by implementing the quality control procedures at every stage of production to final inspection from incoming raw material to finish products.



RESEARCH & DEVELOPMENT:

With our long experience, expertise and continues Research & Development with incorporation of advanced technology and high-tech cutting-edge machineries, **DAWSONS-TECH** is committed to constant upgradation and expand its product range to meet the requirements of its customer to their entire satisfaction at every time.

CUSTOMER SATISFACTION:

We strive to achieve total customer satisfaction and continuously work to set higher goals to provide the reliable quality, timely delivery of our products and prompt services in the best interest of our customers with very competitive price.

BSPP 60° CONE FITTINGS

General Information:

DAWSONS-TECH 60° Cone design Fittings with BSP (Parallel) thread are generally used with Hose and Tubing connections in Hydraulic systems.

Features / Benefits :

- BSPP 60° Cone Fittings design according to BS5200.
- Straight Fittings are manufactured from Bar Stock.
- Shape Fittings are manufactured from Forged Body.
- The seat angle is 60° with BSPP (Parallel) thread.
- Precisely manufactured to ensure perfect seal by Metal to Metal line of contact.
- · Available in Material SS316L.



Product Range & Operating Parameters:

Pressure Rating : Upto 3000 PSIG (206 BAR) **End Connections - Fractional**: 1/4" to 1" BSPP (Parallel) Threads.

Applications:

Hydraulic

INDEX



Male Union Elbow (BSP (Parallel) Thread) Page No. 4



Male Union Tee (BSP (Parallel) Thread) Page No. 4



Male to Swivel Female Elbow (BSP (Parallel) Thread) Page No. 4



Male to Swivel Female Run Tee (BSP (Parallel) Thread) Page No. 4



Male to Swivel Female Branch Tee (BSP (Parallel) Thread)

Page No. 5




Female Swivel Union Elbow (BSP (Parallel) Thread) Page No. 5



Female Swivel Union Tee (BSP (Parallel) Thread) Page No. 5



Male Adapter (BSP (Parallel) Thread) Page No. 5



Bulkhead Male Adapter (BSP (Parallel) Thread) Page No. 6



Hex Plug (BSP (Parallel) Thread) Page No. 6



Male to Female Hose Adapter (BSP (Parallel) to NPT Thread)

Page No. 7



(BSP (Parallel) to BSP (Taper) Thread)

Male - Female Hose Adapter Page No. 7



Female Swivel Union (BSP (Parallel) Thread) Page No. 6

Page No. 8



Swivel Female Cap

(BSP (Parallel) Thread)

Page No. 6



Male to Femal Hose Adapter

(BSP (Parallel) Thread)

Page No. 7


Male Adapter 'OR' (BSP (Parallel) to NPT Thread) (BSP (Parallel) to BSP (Taper) Thread) (BSP (Parallel) to BSP (Parallel) Thread)



Reducing Male Adapter (BSP (Parallel) Thread) Page No. 9



Male to Swivel Female Adapter (BSP (Parallel) Thread to Swivel Nut) Page No. 9




Page No. 8



Page No. 9








Male Union Elbow (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech			
Р	Α	С	D	A/F	Part No.
1/8	25.4	8.1	3.5	11.1	60MUE-2G
1/4	25.4	11.1	5.1	14.2	60MUE-4G
3/8	285	12.1	8.1	17.4	60MUE-6G
1/2	32.5	14.1	11.1	22.2	60MUE-8G?
5/8	36.5	16.1	14.3	24.0	60MUE-10G
3/4	41.3	16.1	16.6	27.0	60MUE-12G
1	44.5	19.1	22.2	35.0	60MUE-16G

Dimensions are for reference only and are subject to change.






Male Union Tee (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech			
Р	Α	С	D	A/F	Part No.
1/8	22.2	8.0	3.5	11.1	60MUT-2G
1/4	22.2	11.0	4.7	14.2	60MUT-4G
3/8	25.4	12.0	8.1	17.4	60MUT-6G
1/2	30.5	14.0	11.1	22.2	60MUT-8G?
5/8	31.	16.0	14.2	24.0	60MUT-10G
3/4	38.1	16.0	16.6	27.0	60MUT-12G
1	44.4	19.0	22.2	35.0	60MUT-16G

Dimensions are for reference only and are subject to change.






Male to Swivel Female Elbow (BSP (Parallel) Thread)

IVIAIC to SW	viale to swiver remaie Libow (BSI (Faraniei) Thread)							
BSPP Thread Size			Dawsons-Tech Part No.					
Р	Α	В	С	D	E	A/F1	A/F2	Part No.
1/8	25.4	25.4	8.1	3.5	4.1	11.1	14.3	60MSFE-2G
1/4	25.4	28.6	11.1	5.1	4.2	14.2	19.0	60MSFE-4G
3/8	28.5	31.5	12.1	7.2	1.6	17.4	22.2	60MSFE-6G
1/2	32.5	31.5	14.1	11.1	6.8	22.2	27.0	60MSFE-8G?
5/8	36.5	37.3	16.1	12.7	10.1	24.0	30.0	60MSFE-10G
3/4	41.3	42.5	16.1	15.5	8.7	27.0	31.7	60MSFE-12G
1	44.5	44.5	19.1	19.8	10.1	35.0	38.1	60MSFE-16G

Dimensions are for reference only and are subject to change.






Male to Swivel Female Run Tee (BSP (Parallel) Thread)

BSPP Thread Size			Dawsons-Tech Part No.					
Р	Α	В	С	D	E	A/F1	A/F2	Part No.
1/8	22.2	25.4	8.0	3.5	4.1	11.1	14.3	60MSFRT-2G
1/4	22.2	28.6	11.0	4.7	4.2	14.2	19.0	60MSFRT-4G
3/8	25.4	31.7	12.0	8.1	4.6	17.4	22.2	60MSFRT-6G
1/2	30.5	35.5	14.0	11.1	6.8	22.2	27.0	60MSFRT-8G?
5/8	31.7	40.1	16.0	14.2	10.1	24.0	30.0	60MSFRT-10G
3/4	38.1	42.5	16.0	16.6	8.7	27.0	31.7	60MSFRT-12G
1	44.4	50.1	19.0	22.2	10.1	35.0	38.1	60MSFRT-16G








Male to Swivel Female Branch Tee (BSP (Parallel) Thread)

BSPP Thread Size			Dawsons-Tech Part No.					
Р	Α	В	С	D	E	A/F1	A/F2	Part No.
1/8	22.2	25.4	8.0	3.5	4.1	11.1	14.3	60MSFBT-2G
1/4	22.2	28.6	11.0	4.7	4.2	14.2	19.0	60MSFBT-4G
3/8	25.4	31.7	12.0	8.1	4.6	17.4	22.2	60MSFBT-6G
1/2	30.5	35.5	14.0	11.1	6.8	22.2	27.0	60MSFBT-8G?
5/8	31.7	40.1	16.0	14.2	10.1	24.0	30.0	60MSFBT-10G
3/4	38.1	42.5	16.0	16.6	8.7	27.0	31.7	60MSFBT-12G
1	44.4	50.1	19.0	22.2	10.1	35.0	38.1	60MSFBT-16G

Dimensions are for reference only and are subject to change.






Female Swivel Union Elbow (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech Part No.				
Р	В	D	E	A/F1	A/F2	Part No.
1/8	25.4	3.5	4.1	11.1	14.3	60FSUE-2RG
1/4	28.6	4.7	4.2	14.2	19.0	60FSUE-4RG
3/8	31.5	8.1	1.6	17.4	22.2	60FSUE-6RG
1/2	31.5	11.1	6.8	22.2	27.0	60FSUE-8RG?
5/8	37.3	14.2	10.1	24.0	30.0	60FSUE-10RG
3/4	42.5	16.6	8.7	27.0	31.7	60FSUE-12RG
1	49.5	22.2	10.1	35.0	38.1	60FSUE-16RG

Dimensions are for reference only and are subject to change.






Female Swivel Union Tee (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech Part No.				
Р	Α	D	E	A/F1	A/F2	Part No.
1/8	25.4	3.5	4.1	11.1	14.3	60FSUT-2RG
1/4	25.4	4.7	4.2	14.2	19.0	60FSUT-4RG
3/8	31.7	8.1	4.6	17.4	22.2	60FSUT-6RG
1/2	36.1	11.1	6.8	22.2	27.0	60FSUT-8RG?
5/8	37.1	14.2	10.1	24.0	30.0	60FSUT-10RG
3/4	42.5	16.6	8.7	27.0	31.7	60FSUT-12RG
1	48.8	22.2	10.1	35.0	38.1	60FSUT-16RG

Dimensions are for reference only and are subject to change.






Male Adapter (BSP (Parallel) Thread)

Trail Flad Petr (BSF (Faranci) Frieda)								
BSPP Thread Size		Dawsons-Tech						
Р	Α	С	D	A/F	Part No.			
1/8	21.1	8.1	3.5	12.7	60MA-2G			
1/4	29.1	11.1	5.1	15.9	60MA-4G			
3/8	32.1	12.1	8.1	19.0	60MA-6G			
1/2	38.1	14.1	11.1	22.2	60MA-8G?			
5/8	44.1	16.1	14.3	24.0	60MA-10G			
3/4	44.1	16.1	16.6	28.6	60MA-12G			
1	50.1	19.1	22.2	34.9	60MA-16G			








Bulkhead Male Adapter (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech Part No.					
Р	Α	В	С	D	A/F1	A/F2	Part No.
1/8	41.1	28.1	8.1	3.5	14.3	14.3	60BMA-2G
1/4	16.1	28.1	11.1	5.1	19.0	19.0	60BMA-4G
3/8	52.1	32.1	12.1	8.1	22.2	22.2	60BMA-6G
1/2	59.1	35.1	14.1	11.1	27.0	27.0	60BMA-8G?
5/8	63.1	35.1	16.1	14.3	30.0	30.0	60BMA-10G
3/4	66.1	38.1	16.1	16.6	31.7	31.7	60BMA-12G
1	72.1	41.1	19.1	22.2.	41.3	41.3	60BMA-16G

Dimensions are for reference only and are subject to change.






Hex Plug (BSP (Parallel) Thread)

BSPP Thread Size	D	Dawsons-Tech Part No.		
Р	Α	С	A/F	Part No.
1/8	13.1	8.1	12.7	60HP-2G
1/4	18.1	11.1	17.4	60HP-4G
3/8	20.1	12.1	20.6	60HP-6G
1/2	24.1	14.1	25.4	60HP-8G?
5/8	28.1	16.1	28.6	60HP-10G
3/4	28.1	16.1	30.0	60HP-12G
1	31.1	19.1	35.0	60HP-16G

Dimensions are for reference only and are subject to change.






Female Swivel Union (BSP (Parallel) Thread)

BSPP Thread Size		Dawsons-Tech Part No.			
Р	Α	D	Е	A/F	Part No.
1/8	23.1	3.5	4.1	14.3	60FSU-2RG
1/4	25.6	4.7	4.2	18.1	60FSU-4RG
3/8	31.2	8.1	4.6	22.2	60FSU-6RG
1/2	29.7	11.1	6.8	25.6	60FSU-8RG?
5/8	36.3	14.2	10.1	28.6	60FSU-10RG
3/4	40.8	16.6	8.7	31.7	60FSU-12RG
1	39.6	22.2	10.1	38.1	60FSU-16RG

Dimensions are for reference only and are subject to change.






Female Cap (BSP (Parallel) Thread)

BSPP Thread Size	D	Dawsons-Tech Part No.		
Р	Α	E	A/F	Part No.
1/8	14.8	4.1	14.3	60FC-2RG
1/4	17.8	4.2	19.0	60FC-4RG
3/8	20.6	4.6	22.2	60FC-6RG
1/2	21.4	6.8	27.0	60FC-8RG?
5/8	20.6	10.1	30.0	60FC-10RG
3/4	25.8	8.7	31.7	60FC-12RG
1	30.9	10.1	41.2	60FC-16RG








Male to Female Hose Adapter (BSP (Parallel) Thread)

Male BSPP Thread Size	Female BSPP Thread Size	D	Dimensions in mm			Dawsons-Tech Part No.
P1	P2	Α	С	D	A/F	Part No.
1/8	1/8	24.1	8.1	3.5	14.2	60HB-2G-2RG
1/8	1/4	27.1	8.1	3.5.	19.0	60HB-2G-4RG
1/4	1/8	27.1	11.1	4.7	15.9	60HB-4G-2RG
1/4	1/4	31.1	11.1	4.7	19.0	60HB-4G-4RG
1/4	3/8	33.1	11.1	4.7	22.2	60HB-4G-6RG
3/8	1/4	32.1	12.1	8.1	19.0	60HB-6G-4RG
3/8	3/8	34.1	12.1	8.1	22.2	60HB-6G-6RG
3/8	1/2	37.1	12.1	8.1	27.0	60HB-6G-8RG
1/2	3/8	36.1	14.1	11.1	22.2	60HB-8G-6RG
1/2	1/2	39.1	14.1	11.1	27.0	60HB-8G-8RG
1/2	3/4	44.1	14.1	11.1	31.7	60HB-8G-12RG
5/8	5/8	44.1	16.1	14.3	30.0	60HB-10G-10RG
3/4	1/2	41.1	16.1	16.6	27.0	60HB-12G-10RG
3/4	3/4	46.1	16.1	16.6	31.7	60HB-12G-10RG?
3/4	1	50.1	16.1	16.6	41.3	60HB-12G-16RG
1	3/4	49.1	19.1	22.2	34.9	60HB-16G-12RG
1	1	51.1	19.1	22.2	41.3	60HB-16G-16RG

Dimensions are for reference only and are subject to change.






Male to Female Hose Adapter (BSP (Parallel) to NPT Thread)

Male BSPP Thread Size	Female NPT Thread Size	Dimensions in mm				Dawsons-Tech
P1	P2	Α	С	D	A/F	Part No.
1/8	1/8	25.4	8.1	3.5	12.7	60HB-2G-2N
1/4	1/4	33.2	11.1	4.7	19.0	60HB-4G-4N
3/8	3/8	36.1	12.1	8.1	22.2	60HB-6G-6N
1/2	1/2	41.1	14.1	11.1	27.0	60HB-8G-8N
5/8	1/2	43.1	16.1	14.3	30.0	60HB-10G-10N
3/4	3/4	46.1	16.1	16.6	31.75	60HB-12G-12N
1	1	55.1	19.1	22.2	41.3	60HB-16G-16N

Dimensions are for reference only and are subject to change.






Male to Female Hose Adapter (BSP (Parallel) to BSP (Taper) Thread)

Male BSPP Thread Size	Female BSPT Thread Size	Dimensions in mm			Dawsons-Tech Part No.	
P1	P2	Α	С	D	A/F	Part No.
1/8	1/8	25.4	8.1	3.5	12.7	60HB-2G-2RT
1/4	1/4	33.2	11.1	4.7	19.0	60HB-4G-4RT
3/8	3/8	36.1	12.1	8.1	22.2	60HB-6G-6RT
1/2	1/2	41.1	14.1	11.1	27.0	60HB-8G-8RT
5/8	1/2	43.1	16.1	14.3	27.0	60HB-10G-10RT
3/4	3/4	46.1	16.1	16.6	31.75	60HB-12G-12RT
1	1	55.1	19.1	22.2	41.3	60HB-16G-16RT








Male Adapter (BSP (Parallel) to NPT Thread)

BSPP	NPT Thread Size			mensi		mm		Dawsons-Tech Part No.
P1	P2	Α	В	С	D1	D2	A/F	Tare No.
1/8	1/8	23.1	10.1	8.1	3.5	5.5	12.7	60MA-2G-2N
1/8	1/4	26.1	13.1	8.1	3.5	7.5	15.9	60MA-2G-4N
1/4	1/8	28.1	10.1	11.1	4.7	4.7	15.9	60MA-4G-2N
1/4	1/4	31.1	13.1	11.1	4.7	7.5	15.9	60MA-4G-4N
1/4	3/8	32.1	14.1	11.1	4.7	10.0	19.0	60MA-4G-6N
1/4	1/2	35.1	17.1	11.1	4.7	13.5	22.2	60MA-6G-8N
3/8	1/8	30.1	10.1	12.1	8.1	4.7	19.0	60MA-6G-2N
3/8	1/4	32.7	12.7	12.1	7.5	7.5	19.0	60MA-6G-4N
3/8	3/8	33.1	13.1	12.1	8.1	10.7	19.0	60MA-6G-6N
3/8	1/2	35.7	15.9	12.1	8.1	13.5	22.2	60MA-6G-8N
1/2	1/4	36.7	12.7	14.1	11.1	7.5	22.2	60MA-8G-4N
1/2	3/8	37.1	13.1	14.1	11.1	11.1	22.2	60MA-8G-6N
1/2	1/2	40.1	16.1	14.1	11.1	13.5	22.2	60MA-8G-8N
1/2	3/4	42.1	18.1	14.1	11.1	19.1	28.6	60MA-8G-12N
1/2	1	48.2	22.2	14.1	11.1	23.8	34.9	60MA-8G-16N
5/8	1/2	44.1	16.1	16.1	13.5	13.5	28.6	60MA-10G-8N
3/4	1/2	45.1	17.1	16.1	16.6	13.5	31.7	60MA-12G-8N
3/4	3/4	47.1	19.1	16.1	16.6	18.6	31.7	60MA-12G-12N
3/4	1	50.1	22.1	16.1	16.6	23.8	34.9	60MA-12G-16N
1	1/2	47.1	16.1	19.1	22.2	13.5	34.9	60MA-16G-8N
1	3/4	51.1	20.1	19.1	20.6	19.1	34.9	60MA-16G-12N
1	1	53.2	22.2	19.1	22.2	23.8	34.9	60MA-16G-16N

Dimensions are for reference only and are subject to change.






Male Adapter (BSP (Parallel) to BSP (Taper) Thread)

BSPP Thread Size	BSPT Thread Size	.,			ons in			Dawsons-Tech Part No.
P1	P2	Α	В	С	D1	D2	A/F	Tare No.
1/8	1/8	23.1	10.1	8.1	3.5	5.5	12.7	60MA-2G-2RT
1/8	1/4	26.1	13.1	8.1	3.5.	7.5	15.9	60MA-2G-4RT
1/4	1/8	28.1	10.1	11.1	4.7	4.7	15.9	60MA-4G-2RT
1/4	1/4	31.1	13.1	11.1	4.7	7.5	15.9	60MA-4G-4RT
1/4	3/8	32.1	14.1	11.1	4.7	10.0	19.0	60MA-4G-6RT
1/4	1/2	35.1	17.1	11.1	4.7	13.5	22.2	60MA-6G-8RT
3/8	1/8	30.1	10.1	12.1	8.1	4.7	19.0	60MA-6G-2RT
3/8	1/4	32.7	12.7	12.1	7.5	7.5	19.0	60MA-6G-4RT
3/8	3/8	33.1	13.1	12.1	8.1	10.7	19.0	60MA-6G-6RT
3/8	1/2	35.7	15.9	12.1	8.1	13.5	22.2	60MA-6G-8RT
1/2	1/4	36.7	12.7	14.1	11.1	7.5	22.2	60MA-8G-4RT
1/2	3/8	37.1	13.1	14.1	11.1	11.1	22.2	60MA-8G-6RT
1/2	1/2	40.1	16.1	14.1	11.1	13.5	22.2	60MA-8G-8RT
1/2	3/4	42.1	18.1	14.1	11.1	19.1	28.6	60MA-8G-12RT
1/2	1	48.2	22.2	14.1	11.1	23.8	34.9	60MA-8G-16RT
5/8	1/2	44.1	16.1	16.1	13.5	13.5	28.6	60MA-10G-8RT
3/4	1/2	45.1	17.1	16.1	16.6	13.5	31.7	60MA-12G-8RT
3/4	3/4	47.1	19.1	16.1	16.6	18.6	31.7	60MA-12G-12RT
3/4	1	50.1	22.1	16.1	16.6	23.8	34.9	60MA-12G-16RT
1	1/2	47.1	16.1	19.1	22.2	13.5	34.9	60MA-16G-8RT
1	3/4	51.1	20.1	19.1	20.6	19.1	34.9	60MA-16G-12RT
1	1	53.2	22.2	19.1	22.2	23.8	34.9	60MA-16G-16RT










BSPP Thread Size	BSPP Thread Size	Dimensions in mm Dawsons-Te					
P1	P2	Α	В	С	D	A/F	Part No.
1/8	1/8	25.5	7.4	8.1	3.5	14.3	60MA-2G-2G-OR
1/4	1/4	31.1	11.1	11.1	5.1	19.0	60MA-4G-4G-OR
3/8	3/8	34.1	12.1	12.1	8.1	22.2	60MA-6G-6G-OR
1/2	1/2	42.1	15.1	14.1	11.1	28.6	60MA-8G-8G-OR
5/8	5/8	47.1	16.1	16.1	14.3	30.0	60MA-10G-10G-OR
3/4	3/4	47.1	16.1	16.1	15.9	31.7	60MA-12G-12G-OR
1	1	47.1	19.1	19.1	22.2	41.3	60MA-16G-16G-OR

Dimensions are for reference only and are subject to change.






Reducing Male Adapter (BSP (Parallel) to BSP (Parallel) Thread)

BSPP Thread Size	BSPP	`	Dimensions in mm					Dawsons-Tech Part No.
P1	P2	Α	C1	C2	D1	D2	A/F	Part NO.
1/4	1/8	26.1	8.1	11.1	3.5	4.7	15.9	60RMA-4G-2G
3/8	1/8	28.1	8.1	12.1	3.5	7.9	19.0	60RMA-6G-2G
3/8	1/4	31.1	11.1	12.1	4.7	7.9	19.0	60RMA-6G-4G
1/2	1/4	35.1	11.1	14.1	4.7	11.1	22.2	60RMA-8G-4G
1/2	3/8	36.1	12.1	14.1	7.9	11.1	22.2	60RMA-8G-6G
5/8	1/2	42.1	14.1	16.1	11.1	14.2	24.0	60RMA-10G-8G
3/4	1/4	39.1	11.1	16.1	4.7	16.6	28.6	60RMA-12G-4G
3/4	3/8	40.1	12.1	16.1	7.9	16.6	28.6	60RMA-12G-6G
3/4	1/2	42.1	14.1	16.1	11.1	16.6	28.6	60RMA-12G-8G
3/4	5/8	44.1	16.1	16.1	14.2	16.6	28.6	60RMA-12G-10G
1	3/8	43.1	12.1	19.1	7.9	22.2	34.9	60RMA-16G-6G
1	1/2	45.1	14.1	19.1	11.1	22.2	34.9	60RMA-16G-8G
1	3/4	47.1	16.1	19.1	16.6	22.2	34.9	60RMA-16G-12G

Dimensions are for reference only and are subject to change.





Male to Swivel Female Adapter (BSP (Parallel) Thread to Swivel Nut)

Male BSPP Thread Size	Female BSPP Thread Size		Diı	mensio	ns in n	nm		Dawsons-Tech Part No.
P1	P2	Α	С	D	Ε	A/F1	A/F2	rait No.
1/8	1/8	30.2	8.1	3.5	4.1	12.7	14.2	60FSMA-2G-2RG
1/4	1/8	35.2	11.1	4.7	4.1	14.2	14.2	60FSMA-4G-2RG
1/8	1/4	31.2	8.1	3.5	4.2	15.9	19.0	60FSMA-2G-4RG
1/4	1/4	37.2	11.1	4.7	4.2	15.9	19.0	60FSMA-4G-4RG
3/8	1/4	38.6	12.1	8.1	4.2	19.0	19.0	60FSMA-6G-2RG
1/4	3/8	39.8	11.1	4.7	4.6	22.2	22.2	60FSMA-4G-6RG
3/8	3/8	41.7	12.1	8.1	4.6	22.2	22.2	60FSMA-6G-6RG
1/2	3/8	45.4	14.1	11.1	4.6	22.2	22.2	60FSMA-8G-6RG
1/4	1/2	41.9	11.1	4.7	6.8	25.4	27.0	60FSMA-4G-8RG
3/8	1/2	42.9	12.1	8.1	6.8	25.4	27.0	60FSMA-6G-8RG
1/2	1/2	47.3	14.1	11.1	6.8	25.4	27.0	60FSMA-8G-8RG
5/8	1/2	49.2	16.1	14.2	6.8	25.6	27.0	60FSMA-10G-8RG
3/4	1/2	49.2	16.1	16.6	6.8	28.6	27.0	60FSMA-12G-8RG
1/2	5/8	49.3	14.1	11.1	10.1	25.4	30.0	60FSMA-8G-10RG
5/8	5/8	57.7	16.1	14.2	10.1	27.0	30.0	60FSMA-10G-10RG
3/4	5/8	53.5	16.1	16.6	10.1	28.6	30.0	60FSMA-12G-10RG
1/2	3/4	50.8	14.1	11.1	8.7	31.7	31.7	60FSMA-8G-12RG
5/8	3/4	54.2	16.1	14.2	8.7	27.0	31.7	60FSMA-10G-12RG
3/4	3/4	52.6	16.1	16.6	8.7	27.0	31.7	60FSMA-12G-12RG
1	3/4	57.2	19.1	22.2	8.7	34.9	31.7	60FSMA-16G-12RG
3/4	1	59.3	16.1	16.6	10.1	34.9	41.3	60FSMA-12G-16RG
1	1	62.2	19.1	22.2	10.1	34.9	41.3	60FSMA-16G-16RG



ORDERING INFORMATION

For Example: Part No. MA-8RT-8N-SS

Type of Fittings	End Connection Pipe Thread Size & Type 1	End Connection Pipe Thread Size & Type 2	Material of Construction
MA	8G	8N	SS
Male Adapter	1/2" BSP	1/2" NPT	SS316

PART NO. CODE DESCRIPTION:

	2	1/8″
	4	1/4"
End Connection	6	3/8"
Pipe Thread Size	8	1/2"
Fipe Illiead Size	10	5/8″
	12	3/4"
	16	1"

	N : NPT	
End Connection	RT : BSPT	
Pipe Thread Size	G : BSP (Male)	
	RG : BSP (Female)	

Material of	SS : SS316
Construction	SSL : SS316L

OUR PLEDGE

DAWSONS-TECH is self-committed for continuous development and upgradation of its products to meet the growing demands for Industries requirements of Flow Control Components by advanced technology induction and cutting-edge solution which is in-line with focused objective mission

"TO PROVIDE OUR CUSTOMERS
WITH
CONSISTENT RELIABLE QUALITY PRODUCTS
AT
RIGHT TIME & COMPETITIVE PRICE"

OUR COMPREHENSIVE PRODUCT LINE





Twin Ferrule Tube Fittings



Precision Thread / Weld Pipe Fittings



37° Flare / BSPP 60° Cone Fittings



High Purity Metal Gasket Face Seal Fittings



High Purity 'O' Ring Face Seal Fittings



High Purity Weld Fittings



Instrumentation / UHP Ball Valves



Instrumentation / UHP Check Valves



Instrumentation Needle / Gauge Valves



High Pressure Wellhead Grease / Bleed Fittings



Gauge Cock & Accessories



Quick Connect Couplings



Registered Office and Manufacturing Plant:

DAWSONS-TECH COMPONENTS LLP

Unit No. DD - 6 & 7, Khan Real Industrial Estate, N. H. 08, Pelhar, Vasai Phata, Vasai (East), Dist. Palghar - 401 208, Maharashtra, India.

Mobile: +91-9833355596 Email: info@dawsonstech.com Website: www.dawsonstech.com

LLPIN: AAN-0434

Catalogue No. 60CF-21